

Thermo Scientific Easypure II RF uses pretreated feed water to produce portable ultrapure water for critical applications, including: HPLC, ICP, GC/MS, AA and buffer prep.

## Thermo Scientific Barnstead Easypure II RF

Portable ultrapure water

### Description

The Thermo Scientific Easypure II RF (Reservoir Feed) series was specially designed for scientists who require a portable purification system, capable of producing up to 15 liters of ultrapure water per day from pretreated water.

Offered as two distinct models to suit your specific research needs, our base unit produces ultrapure water suitable for general laboratory applications, whereas the Easypure® II RF/UV has an internal dual wavelength UV lamp to reduce organics to the absolute lowest levels. This is an ideal choice for HPLC, ICP, GC/MS, AA, and related applications.

### Features

- Each system produces ultrapure water that exceeds the quantitative specifications of Type 1 water as described in ASTM D1193, ISO 3696, and CLSI®-CLRW.
- Three cartridges in series provide increased capacity over similar systems.

- A 0.2 micron final filter at the point of use provides water free of particles and bacteria.
- An internal non-contaminating 6.5 liter reservoir allows the system to be mounted in locations without a permanent supply of water. Simply pour pretreated water into the reservoir and the Easypure II will produce ultrapure water anywhere in your laboratory.
- A standby mode recirculates purified water during inactivity to ensure purity and allow for on-demand use.
- All components are constructed of inert materials ensuring maximum ionic and organic purity.
- Whisper quiet pump provides optimal flow rates and silent operation.
- Integral low water and low pressure pump protectors protect the pump in the event feed water is interrupted to the system.
- Feed water must be pretreated by reverse osmosis, distillation, or deionization.



Easypure II RF



Cartridges easily accessible from panel door. Optional wall bracket includes sturdy swivel base for quick access.

Quick Look Comparison		
	Easypure II RF	Easypure II RF/UV
<b>System Design</b>	Base Unit - No UV	Ultra low organics
<b>Application</b>	<ul style="list-style-type: none"> <li>• Buffer prep</li> <li>• Titration solutions</li> <li>• AA</li> <li>• GC</li> </ul>	<ul style="list-style-type: none"> <li>• HPLC</li> <li>• TOC</li> <li>• GC/MS</li> </ul>
<b>Resistivity at 25°C, MΩ-cm</b>	18.2	18.2
<b>Total Organic Carbon, ppb</b>	5-10	1-5
<b>Bacteria, CFU/mL</b>	< 1	< 1
<b>Daily Output, L</b>	Up to 15	Up to 15

## Thermo Scientific Barnstead Easypure II RF Specifications

Product Specifications			
Overall Dimensions W x H x D	Inlet Water Temperature	Voltage	Flow Rate
12 x 17.1 x 19 inches 30.5 x 43.5 x 48.3 cm	40-104 °F 4-40 °C	100-240 VAC	0.8 L/min

## Ordering Information

System Options	Easypure II RF	Easypure II RF/UV
<b>Model Number</b> All systems include a Thermo Scientific Ventgard reservoir cap and a UV lamp (UV model only).	<b>D7031</b>	<b>D7035</b>
<b>Required Accessories</b>		
<b>Cartridge Pack</b> Choose the Cartridge Pack according to your feed water and system.		
Deionized Feed	D502126	D502124
RO or Distilled Feed	D502127	D502125
<b>0.2 micron Final Filter</b>	D3750	D3750
<b>Empty Cartridges for Cleaning</b>	D7034	D7034
<b>Optional Accessory</b>		
<b>Wall Mounting Bracket</b> Recommended when bench space is limited. Sturdy swivel base provides easy access to cartridge door.	D13324	D13324
<b>Replacement Consumables</b>		
<b>Ultraviolet Lamp</b>	n/a	LMX13
<b>Ventgard Reservoir Cap</b> Includes the cap and filter.	CV703X4A	CV703X4A



## Thermo Scientific H<sub>2</sub>O SELECT Water Testing Program

We offer a unique, FREE water test program to analyze your feed water and choose the perfect system for your sensitive applications and procedures.

Visit [www.thermo.com/select](http://www.thermo.com/select) to learn more.

© 2009 Thermo Fisher Scientific Inc. All rights reserved. CLSI is a registered trademark of Clinical and Laboratory Standards Institute. All other trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

**North America:** USA/Canada +1 800 553 0039  
**Europe:** Austria +43 1 801 40 0, Belgium +32 2 482 30 30, France +33 2 2803 2180, Germany national toll free 08001-536 376, Germany international +49 6184 90 6940, Italy +39 02 02 95059 434-254-375, Netherlands +31 76 571 4440, Nordic/Baltic countries +358 9 329 100, Russia/CIS +7 (812) 703 42 15, Spain/Portugal +34 93 223 09 18, Switzerland +41 44 454 12 12, UK/Ireland +44 870 609 9203  
**Asia:** China +86 21 6865 4588 or +86 10 8419 3588, India toll free 1800 22 8374, India +91 22 6716 2200, Japan +81 45 453 9220,  
**Other Asian countries** +852 2885 4613 Countries not listed: +49 6184 90 6940 or +33 2 2803 2180  
 DSWPEIRF0209

[www.thermo.com/purewater](http://www.thermo.com/purewater)